

PLASMA 1565 LCD INVERTER



The three-phase compressed air plasma metal cutting power source, **PLASMA 1565 LCD INVERTER** features an innovative **SYNERGIC interface** that automatically sets the cutting parameters according to the information received from the operator regarding the material being processed and the selected process.

The machine can automatically handle two different torches with the possibility of different lengths: ECF-71, ECF-181.

It is particularly suitable for heavy duty carpentry applications and for continuous work cycles, for manual and automatic manufacturing in industry and handicrafts.

The ignition of the pilot arc without HF allows you to work near computers or, in any case, equipment sensitive to high-frequency emissions such as electromedical equipment.

It may be powered by motor generators of suitable power.

It offers the possibility to activate a security password.

Equipped with safety systems on the torch head and in the machine side adapter.

Its standard equipment includes a 6 metre-long hand torch ECF-181 and a grounding cable.

VARIOUS DISPLAY IMAGES



PLASMA 1565
LCD INVERTER
with trolley
item 580007

MAIN FEATURES

- **Auto-Set** function, used to automatically select the power supply voltage in the following range: 3x208/220/230V and 400/440V.
- **Low Pilot Arc** technology which thanks to the special shape of the plasma chamber, together with an innovative power source and an ignition system without high frequency, allow the pilot arc to be kept on longer, without comprising the duration of the consumables.
- **Pilot Arc Time** function that controls the duration of the pilot arc in an automatic or adjustable manner.
- **Pilot Arc Length** function that controls the length of the pilot arc in an automatic or adjustable manner.
- **Exhaust Electrode** function that controls the electrode consumption and warns the operator that the consumables need replacing, which can be set automatically or adjusted in percentage.
- **Save Post Gas** function that controls the torch cooling and gas consumption, in an automatic or adjustable manner.
- **Input Power** function used to set the input power absorbed thus automatically limiting the output cutting current, adapting the power source to all the sizes of the industrial plants.

PLASMA 1565 LCD INVERTER



- **Self Restart Pilot** function for cutting netting and grates.
- **Synergic Interface** function that lets the power source adjust the cutting parameters automatically.
- **Cartridge Spring** technology (Patented), which reduces the internal moving parts of the torches, increasing their reliability over time.
- **Ultra Cut Capacity** technology that increases the cutting capacity on high thickness materials.
- **Innovative Thin Cut** technology that ensures higher quality cutting and reduced Kerf (amount of removed material).
- **Hyper Speed Cut** technology that increases the cutting speed.
- **Multi Piercing** technology possibility of piercing on high thickness materials in less time and with less wear of consumables.
- **Extra Life** technology to increase the performance and service life of consumables.
- **Long Tip Cut** technology.
- It is available, as an optional, an interface kit that activates the **V-out Voltage CNC** function to control an electronic output cutting voltage divider to be adjusted from 1/20V to 1/100V and the **Remote Current CNC** function to remotely control the cutting current adjustment with 0-10V isolated voltage.

TECHNICAL DATA

		PLASMA 1565 LCD INVERTER			
	Item	PLASMA 1565 LCD INVERTER			
	Code	P00443			
	Input Voltage	3x208/220/230V 50-60Hz		3x400/440V 50-60 Hz	
	Absorbed power	30% 27 kVA	60% 24 kVA	100% 21 kVA	60% 27kVA 100% 24 kVA
	Current range	10 ÷ 150 A		10 ÷ 150 A	
	Duty cycle	30% 150A	60% 130A	100% 115A	60% 150A 100% 130A
	Max. cut thickness (steel)	45 - 50 mm			
	Coarse cutting capacity	70 mm			
	Stepless regulation	ELECTRONIC			
	Compressed air consumption	360 l/min (6,0 bar)			
	Protection class	IP23			
	Construction standards	EN60974-1 EN60974-7 EN60974-10 SCC			
	Dimensions	330x710x540 h mm			
	Weight	50 kg			

We reserve the right to modify